


# SUPERSEAL

## Brushstrip in carrier

### Rebate standard range



Superseal is manufactured in hardwearing nylon filament fitted with a durable mill finish aluminium carrier.

#### Features

- Two nominal section sizes
- 2m, 2.5m and 3m standard lengths
- Brush heights up to 38mm
- Modified lengths, brush heights and finishes available on request

### Light duty


Type	Carrier dimensions		Brush height BH	Fill material	Part number		
	S	T			2m length	2.5m length	3m length
AP	5.50	5.50	10.00	Nylon black 0.15	H610AP2014	H610AP2514	H610AP3014
			15.00	Nylon black 0.15	H610AP2019	H610AP2519	H610AP3019
BP	7.50	6.50	13.50	Nylon black 0.15	H610BP2019	H610BP2519	H610BP3019
			19.00	Nylon black 0.15	H610BP2025	H610BP2525	H610BP3025
			26.00	Nylon black 0.15	H610BP2032	H610BP2532	H610BP3032
			38.00	Nylon black 0.15	H610BP2044	H610BP2544	H610BP3044

All dimensions are in mm

#### How to specify

Select the required brush height (BH) according to the size of gap to be sealed. For modified products, select the standard part number and specify:

- ▶ Modified length (A)
- ▶ Brush height (BH)



#### Technical notes

##### Cutting to length

Superseal brushstrip should be removed from the aluminium carrier and cut to length with side action croppers to ensure the ends are completely resealed and avoid spillage of the nylon filaments.

Aluminium carriers should be cut to length with a fine tooth saw and deburred. File a lead-in at one end of the carrier to aid assembly of the brushstrip.

##### Fitting

Superseal should be fitted with the tips of the filaments in firm contact with the mating surface but barely flexed. Press fit or use adhesive to fit the seal flush within a pre-machined matching rebate.



Kleeneze Sealtech Limited  
Ansteys Road  
Hanham  
Bristol  
BS15 3SS  
UK

T: +44 (0)117 958 2450  
F: +44 (0)117 960 0141  
E: sales@ksltd.uk.com  
www.ksltd.com

**SUPERSEAL**



Kleeneze Sealtech Limited  
Ansteys Road  
Hanham  
Bristol  
BS15 3SS  
UK

T: +44 (0)117 958 2450  
F: +44 (0)117 960 0141  
E: [sales@ksltd.uk.com](mailto:sales@ksltd.uk.com)  
[www.ksltd.com](http://www.ksltd.com)